Version with marking to show changes made.

5

10

15

20

25

Claim 1. (Amended) A sports racket, comprising;

a frame defining a rounded opening of predetermined shape with a vertical axis and a horizontal axis;

a handle secured to the frame and lying at least substantially along the vertical axis; and strings supported by the frame and suspended within said opening, said strings being arranged in two parallel, interwoven groups, wherein strings of the first group intersect a reference line parallel to the horizontal axis at an angle of about 49-60 degrees above said reference line and strings of the second group intersect the reference line at an angle of about 49-60 degrees below the reference line, the intersection angle is selected to completely eliminate distortion.

Cancel Claim 7

Claim 10. (Amended) A method for diagonal stringing of a sports racket, said strings being arranged in two parallel intersecting groups, said method comprising:

creating a diagonal stringing pattern with a nominal intersection angle between the strings, including a representation of at least substantially all strings of the racket to be strung;

applying said stringing pattern to a first racket frame of a construction type;

determining an intersection point for each string representation with the frame;

providing string holes in the frame at said intersection points;

stringing the racket through said string holes;

tensioning the strings and measuring distortion of the frame;

10

5

re-stringing the racket to eliminate any measured distortion, said re-stringing comprising changing the intersection angle between the strings by passing each string through a hole offset from the hole corresponding to the nominal intersection angle in said stringing pattern, while maintaining said strings in each group in parallel relationship;

15

re-tensioning the strings; and

20

measuring distortion and re-stringing so that said strings are arranged in two

parallel, interwoven groups, wherein strings of the first group intersect a

reference line parallel to the horizontal axis at an angle of about 49-60

degrees above said reference line and strings of the second group intersect

the reference line at an angle of about 49-60 degrees below the reference

line, in order to achieve an angular relationship, whereby frame is not distorted.[as required to eliminate distortion of the frame.]

Claim 15. (Added)

A sports racket, comprising;

a frame defining a rounded opening of predetermined shape with a vertical axis and a horizontal axis;

a handle secured to the frame and lying at least substantially along the vertical

axis; and strings supported by the frame and suspended within said

opening, said strings being arranged in two parallel, interwoven groups,

wherein strings of the first group intersect a reference line parallel to the

horizontal axis at an angle of about 49-60 degrees above said reference

line and strings of the second group intersect the reference line at an angle

of about 49-60 degrees below the reference line, with said strings having

been restrung and re-tensioned in order to achieve said angular

relationships, whereby the frame is not distorted.

20

15

5

10

25